

Ultra Low Power Voltage Detector

■ FEATURES

- Ultra-Low Quiescent Current.
- 1.5V to 10.0V Input Voltage Operation.
- Flexible Detection Voltage Setting
0.1V Step in the Range of 1.6V to 6.0V
- High Detection Voltage Accuracy at $\pm 2.5\%$.
- Built-In Detection Voltage Hysteresis.
- Three Output Types: N-ch, P-ch and CMOS.
- Space Saving Packages: TO-92, SOT-89, SOT-23 and SOT23-5.

■ APPLICATIONS


- Battery Checker for Battery-Operated Systems.
- CPU & Logic Circuit Reset.
- Memory Back-up Circuit.
- Level Discriminator.
- Power Failure Detector.

■ DESCRIPTION

The AIC1680 is an accurate, ultra-low power consumption voltage detector IC, fabricated with advanced CMOS process. The AIC1680 consists of a comparator, a voltage reference unit, a resistor divider, two output drivers, and a hysteresis circuit.

The consumption current is so low that it can often be ignored when compared to the battery self-discharge current. The values of detection and hysteresis voltage are set internally and are accurately controlled by trimming techniques. There are three types of output: N-ch open-drain, P-ch open-drain, and CMOS. Four types of package, TO-92, SOT-89, SOT-23 and SOT-23-5, are available to save board space.

■ TYPICAL APPLICATION CIRCUIT



Voltage Level Indicator (N-ch Open-Drain Output)





■ ORDERING INFORMATION

AIC1680XXXXCX

PACKAGING TYPE
 U: SOT-23
 X: SOT-89
 Z: TO-92
 V:SOT23-5

DETECTION VOLTAGE OPTIONAL
 16: 1.6V
 17: 1.7V
 :
 :
 60: 6.0V

OUTPUT TYPE
 N: N-ch Open Drain
 P: P-ch Open Drain
 C: CMOS

ORDER NUMBER	PIN CONFIGURATION
AIC1680CU (SOT-23)	FRONT VIEW 1: VOUT 2: VDD 3: GND 
AIC1680CX (SOT-89)	FRONT VIEW 1: VOUT 2: VDD 3: GND 
AIC1680CZ (TO-92)	FRONT VIEW 1: VOUT 2: VDD 3: GND 
AIC1680CV (SOT-23-5)	FRONT VIEW 1: VOUT 2: VDD 3: GND 4: NC 5: NC 




■ ABSOLUTE MAXIMUM RATINGS

Supply Voltage	10V
Output Voltage	Vss-0.3 to 10V
Operating Temperature Range	-30°C ~ 80°C
Storage Temperature Range	- 65°C ~ 150°C
Lead Temperature (Soldering) 10 sec.	260°C
Output Current	20mA

■ ELECTRICAL CHARACTERISTICS (Test Conditions : Ta=25°C)

SYMBOL	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{DET}	Detector Voltage		0.975	1.0	1.025	V_{DET}
V_{HYS}	Detector Threshold Hysteresis		0.03	0.05	0.07	V_{DET}
I_{DD}	Supply Current	$V_{DD}=2.0V$ $V_{DD}=3.0V$ $V_{DD}=4.5V$ $V_{DD}=6.0V$ $V_{DD}=10.0V$		0.7 0.9 1.3 1.8 3.2	1.1 1.5 2.0 2.7 4.8	μA
V_{DD}	Operation Voltage		1.5		10	V
I_{OUT} (Nch)	Output Current	$V_{DS}=0.5V$ $V_{DD}=2.4V$ $V_{DS}=0.5V$ $V_{DD}=3.6V$ $V_{DS}=0.5V$ $V_{DD}=4.6V$ $V_{DS}=0.5V$ $V_{DD}=6.0V$		3.24 5.85 7.74 10.44		mA
I_{OUT} (Pch)	Output Current	$V_{DS}=-2.1V$ $V_{DD}=4.5V$		3.5		mA
	Temperature Coeficience			± 150		ppm/ $^{\circ}C$
T_{DELAY}	Output Delay Time				200	μs

■ BLOCK DIAGRAM




■ PIN DESCRIPTIONS

V_{DD}: Power Supply and Detected Voltage Input.



GND: Ground.

V_{out}: Detector Output





■ TYPICAL PERFORMANCE CHARACTERISTICS





N-ch Driver Sinking Current vs. V_{DS}




■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)



P-ch Driver Output Current vs. V_{DS}




■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)



■ APPLICATION INFORMATIONS


The timing diagram of VDD and V_{OUT} is shown in below:

CMOS Type




The guaranteed minimum operation voltage is 1.5V. As the supply voltage(VDD) is reduced below 1.5V, the performance degrades, N-ch or P-ch driving capacity degrades, and the supply current decreases. AIC1680 isn't functioning when VDD down to 0.8V.

NMOS Type



■ PHYSICAL DIMENSIONS

- SOT-23 (unit: mm)




SYMBOL	MIN	MAX
A	1.00	1.30
A1	—	0.10
A2	0.70	0.90
b	0.35	0.50
C	0.10	0.25
D	2.70	3.10
E	1.40	1.80
e	1.90 (TYP)	—
H	2.60	3.00
L	0.37	—
θ_1	1°	9°

- SOT-23 Marking

Part No.	Marking
AIC1680-N16CU	U16N
AIC1680-P16CU	U16P
AIC1680-C16CU	U16C
AIC1680-N17CU	U17N
AIC1680-P17CU	U17P
AIC1680-C17CU	U17C
..... (0.1V INCREMENT)	

Part No.	Marking
AIC1680-N59CU	U59N
AIC1680-P59CU	U59P
AIC1680-C59CU	U59C
AIC1680-N60CU	U60N
AIC1680-P60CU	U60P
AIC1680-C60CU	U60C

- SOT-89 (unit: mm)




SYMBOL	MIN	MAX
A	1.40	1.60
B	0.36	0.48
C	0.35	0.44
D	4.40	4.60
D1	1.62	1.83
E	2.29	2.60
e	1.50 (TYP.)	
e1	3.00 (TYP.)	
H	3.94	4.25
L	0.89	1.20

- SOT-89 Marking

Part No.	Marking
AIC1680-N16CX	X16N
AIC1680-P16CX	X16P
AIC1680-C16CX	X16C
AIC1680-N17CX	X17N
AIC1680-P17CX	X17P
AIC1680-C17CX	X17C
..... (0.1V INCREMENT)	


Part No.	Marking
AIC1680-N59CX	X59N
AIC1680-P59CX	X59P
AIC1680-C59CX	X59C
AIC1680-N60CX	X60N
AIC1680-P60CX	X60P
AIC1680-C60CX	X60C

- TO-92 (unit: mm)



SYMBOL	MIN	MAX
A	4.32	5.33
C	0.38 (TYP.)	
D	4.40	5.20
E	3.17	4.20
e1	1.27 (TYP.)	
L	12.7	-

- SOT-23-5 (unit: mm)



SYMBOL	MIN	MAX
A	1.00	1.30
A1	—	0.10
A2	0.70	0.90
b	0.35	0.50
C	0.10	0.25
D	2.70	3.10
E	1.40	1.80
e	1.90 (TYP)	—
H	2.60	3.00
L	0.37	—
θ1	1°	9°

- SOT-23-5 Marking

Part No.	Marking
AIC1680-N16CV	V16N
AIC1680-P16CV	V16P
AIC1680-C16CV	V16C
AIC1680-N17CV	V17N
AIC1680-P17CV	V17P
AIC1680-C17CV	V17C
..... (0.1V INCREMENT)	

Part No.	Marking
AIC1680-N59CV	V59N
AIC1680-P59CV	V59P
AIC1680-C59CV	V59C
AIC1680-N60CV	V60N
AIC1680-P60CV	V60P
AIC1680-C60CV	V60C