

RF AMPLIFIER

MODEL TM6582

Available as: TM6582, 4 Pin TO-8 (T4)
TN6582, 4 Pin Surface Mount (SM3)
FP6582, 4 Pin Flatpack (FP4)
BX6582, Connectorized Housing (H1)

Features

- Low Noise Figure: 3.5 dB Typical
 - High Output Power: +21 dBm Typical
 - Operating Temp. -55 °C to +85 °C
 - Environmental Screening Available

Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C	
Frequency	20 - 500 MHz	30 - 500 MHz	
Gain (dB)	23	21.5 Min.	
Power @ 1 dB Comp. (dBm)	+21	+17.0	Min.
Reverse Isolation (dB)	- 29	- 27	Max.
VSWR In	1.5:1	2.0:1	Max.
Out	1.25:1	2.0:1	Max.
Noise figure (dB)	3.5	4.5	Max.
Power Vdc	+15	+15	
mA	47	52	Max.

Note: Care should always be taken to effectively ground the case of each unit.







Typical Intermodulation Performance at 25 ° C

- Second Order Harmonic Intercept Point +49 (Typ.)
 Second Order Two Tone Intercept Point +43 (Typ.)
 Third Order Two Tone Intercept Point +33 (Typ.)

Maximum Ratings

Ambient Operating Temperature	-55°C to + 100 °C
Storage Temperature	-62°C to + 125 °C
Case Temperature	+ 125 °C
DC Voltage	+ 18 Volts
Continuous RF Input Power	+10 dBm
Short Term RF Input Power	50 Milliwatts (1 Minute Max.)
Maximum Peak Power	0.5 Watt (3 μsec Max.)

Typical Performance Data



Legend — + 25 °C - - + 85 °C - - - - - -55 °C

Linear S-Parameters

FREQ. MHz	S11		S21		S12		S22	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
20	.36	- 52	13.26	-158	.03	25	.42	120
50	.19	- 57	14.65	165	.03	5	.15	100
100	.16	- 56	14.61	130	.03	- 19	.03	135
200	.20	- 74	13.87	70	.03	- 43	.09	-166
300	.26	-104	13.54	13	.03	- 74	.08	137
400	.29	-144	13.99	- 50	.03	-114	.10	8
500	.29	136	14.49	-129	.03	-174	.10	- 50



2707 Black Lake Place, Philadelphia, PA 19154

TEL 215-464-4000 • • • FAX 215-464-4001 3/17/03