

### Directional Couplers In-Line Style

#### Applications

- Subassemblies
- Lab Systems
- Leveling Loops
- Power Monitoring
- Test and Calibration



#### Features

- Military Grade
- 2.6 - 5.2 GHz
- "In-Line" Configuration
- Connectors Per MIL-C-39012
- Rugged Aluminum Housing
- Built in Termination

#### Electrical Specifications

Model#	Frequency GHz	Coupling dB Mean	Insert. Loss dB Max	Input VSWR Max:1
10610-6	2.6 - 5.2	6.0 ± 0.5	0.50	1.25
10610-10	2.6 - 5.2	10.0 ± 0.5	0.50	1.25
10610-20	2.6 - 5.2	20.0 ± 1.0	0.50	1.25

Model #	Freq. Sems. dB Max	Directivity dB Min/Typ	Max CW Power*	
			Forward	Backward
10610-6	±0.75	18/23	20	2
10610-10	±0.80	18/23	50	5
10610-20	±0.80	18/23	100	50

**Notes: Electrical and Mechanical Specifications subject to change without notice.** Impedance: 50 ohms nominal. Meets MIL-E-5400 Class 3 requirements. Additional screening available for military and space applications. \*These power ratings apply when coupled port VSWR is 2.0:1 or less. Higher power can be handled with a lower VSWR termination. In general the Max CW Power is identical to 3 dB couplers when there is no internal termination or one supplied by Anaren. All models have SMA connectors.

#### Outline Drawing

