

## Aluminum Nitride Terminations

10 Watts, 50  $\Omega$



### Features

- DC – 6.0 GHz
- 10 Watts
- Aluminum Nitride (AlN) Ceramic
- Welded Silver Leads
- Non-Nichrome Resistive Element
- Low VSWR
- 100% Tested

### General Specifications

<b>Resistive Element:</b>	Thick film
<b>Substrate:</b>	Aluminum nitride ceramic
<b>Cover:</b>	Alumina ceramic
<b>Lead(s):</b>	99.99% pure silver (.005" thk)


### Electrical Specifications

<b>Resistance Value:</b>	50 ohms, $\pm 5\%$
<b>Frequency Range:</b>	DC - 6.0 GHz
<b>Power:</b>	10 Watts
<b>V.S.W.R.:</b>	1.25:1

**Notes:** Tolerance is  $\pm 0.010$ , unless otherwise specified. Operating temperature is  $-55^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$  (see chart). Designed to meet or exceed applicable portions of MIL-E-5400. All dimensions are in inches. Lead length 0.15" minimum.

**Specifications subject to change without notice.**

### Outline Drawing



VER. 12/5/01



Available on Tape and Reel for Pick and Place Manufacturing.



Sales Desk USA: Voice: (800) 544-2414 Fax: (315) 432-9121  
Sales Desk Europe: Voice: (+44) 23 92 232392 Fax: (+44) 23 92 251369

# Model RFP-10N50T


# Anaren

## RF Power


### Typical Performance



### Power Derating



### Suggested Mounting Procedures



1. Make sure that the devices are mounted on flat surfaces (.001" under the device) to optimize the heat transfer.
2. Position device on mounting surface and solder in place using an SN96 type solder.
3. Solder leads in place using an SN63 type solder with a controlled temperature iron (700°F).