



PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
25	14m Ω	52A



1. GATE
2. DRAIN
3. SOURCE

ABSOLUTE MAXIMUM RATINGS ($T_C = 25\text{ }^\circ\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Gate-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current	$T_C = 25\text{ }^\circ\text{C}$	I_D	52	A
	$T_C = 100\text{ }^\circ\text{C}$		35	
Pulsed Drain Current ¹		I_{DM}	156	
Avalanche Current		I_{AR}	33	
Avalanche Energy	$L = 0.1\text{mH}$	E_{AS}	250	mJ
Repetitive Avalanche Energy ²	$L = 0.05\text{mH}$	E_{AR}	8.6	
Power Dissipation	$T_C = 25\text{ }^\circ\text{C}$	P_D	45	W
	$T_C = 100\text{ }^\circ\text{C}$		25	
Operating Junction & Storage Temperature Range		T_j, T_{stg}	-55 to 150	$^\circ\text{C}$
Lead Temperature (¹ / ₁₆ " from case for 10 sec.)		T_L	275	

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		2.5	$^\circ\text{C} / \text{W}$
Junction-to-Ambient	$R_{\theta JA}$		65	
Case-to-Heatsink	$R_{\theta CS}$	0.7		

¹Pulse width limited by maximum junction temperature.

²Duty cycle $\leq 1\%$

ELECTRICAL CHARACTERISTICS ($T_C = 25\text{ }^\circ\text{C}$, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$	25			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	1	1.6	3	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0\text{V}, V_{GS} = \pm 20\text{V}$			± 250	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 20\text{V}, V_{GS} = 0\text{V}$			25	μA
		$V_{DS} = 20\text{V}, V_{GS} = 0\text{V}, T_C = 125\text{ }^\circ\text{C}$			250	

On-State Drain Current ¹	$I_{D(ON)}$	$V_{DS} = 10V, V_{GS} = 10V$	60			A
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = 4.5V, I_D = 21A$		16	20	mΩ
		$V_{GS} = 10V, I_D = 26A$		11	14	
Forward Transconductance ¹	g_{fs}	$V_{DS} = 10V, I_D = 26A$		32		S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = 15V, f = 1MHz$		1200	1800	pF
Output Capacitance	C_{oss}			600	1000	
Reverse Transfer Capacitance	C_{rss}			350	500	
Total Gate Charge ²	Q_g	$V_{DS} = 10V, V_{GS} = 10V,$ $I_D = 52A$		35	60	nC
Gate-Source Charge ²	Q_{gs}			8		
Gate-Drain Charge ²	Q_{gd}			5		
Turn-On Delay Time ²	$t_{d(on)}$	$V_{DS} = 15V, R_L = 1\Omega$ $I_D \cong 52A, V_{GS} = 10V, R_{GEN} = 24\Omega$		6	16	nS
Rise Time ²	t_r			120	250	
Turn-Off Delay Time ²	$t_{d(off)}$			40	90	
Fall Time ²	t_f			105	200	
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS ($T_C = 25\text{ }^\circ\text{C}$)						
Continuous Current	I_S				52	A
Pulsed Current ³	I_{SM}				156	
Forward Voltage ¹	V_{SD}	$I_S = 26A, V_{GS} = 0V$		0.9	1.3	V
Reverse Recovery Time	t_{rr}	$I_F = I_S, di_F/dt = 100A / \mu S$		70		nS
Peak Reverse Recovery Current	$I_{RM(REC)}$			200		A
Reverse Recovery Charge	Q_{rr}			0.043		μC

¹Pulse test : Pulse Width $\leq 300\ \mu\text{sec}$, Duty Cycle $\leq 2\%$.

²Independent of operating temperature.

³Pulse width limited by maximum junction temperature.

REMARK: THE PRODUCT MARKED WITH "P48N02LD", DATE CODE or LOT #

TO-252 (DPAK) MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	9.35		10.1	H		0.8	
B	2.2		2.4	I	6.4		6.6
C	0.48		0.6	J	5.2		5.4
D	0.89		1.5	K	0.6		1
E	0.45		0.6	L	0.64		0.9
F	0.03		0.23	M	4.4		4.6
G	6		6.2	N			

