


MMBT3904

Small Signal Transistors (NPN)

SOT-23




Dimensions in inches and (millimeters)

Pin configuration

1 = Base, 2 = Emitter, 3 = Collector.

FEATURES

- ◆ NPN Silicon Epitaxial Planar Transistor for switching and amplifier applications.
- ◆ As complementary type, the PNP transistor MMBT3906 is recommended.
- ◆ This transistor is also available in the TO-92 case with the type designation 2N3904.



MECHANICAL DATA

Case: SOT-23 Plastic Package

Weight: approx. 0.008g

Marking code: 1AM

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

| | SYMBOL | VALUE | UNIT |
|---|-----------------|--|--------------------|
| Collector-Base Voltage | V_{CBO} | 60 | V |
| Collector-Emitter Voltage | V_{CEO} | 40 | V |
| Emitter-Base Voltage | V_{EBO} | 6.0 | V |
| Collector Current | I_C | 200 | mA |
| Power Dissipation at $T_A = 25^\circ\text{C}$ | P_{tot} | 225 ⁽¹⁾ 300 ⁽²⁾ | mW |
| Thermal Resistance Junction to Substrate Backside | $R_{\theta SB}$ | 320 ⁽¹⁾ | $^\circ\text{C/W}$ |
| Thermal Resistance Junction to Ambient Air | $R_{\theta JA}$ | 450 ⁽¹⁾ | $^\circ\text{C/W}$ |
| Junction Temperature | T_j | 150 | $^\circ\text{C}$ |
| Storage Temperature Range | T_S | -65 to +150 | $^\circ\text{C}$ |

NOTES:

(1) Device on fiberglass substrate, see layout.

(2) Device on alumina substrate.

MMBT3904

ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

| | SYMBOL | MIN. | MAX. | UNIT |
|---|--|-----------------------------|-------------------------|-----------------------|
| Collector-Base Breakdown Voltage at $I_C = 10 \mu\text{A}$, $I_E = 0$ | $V_{(BR)CBO}$ | 60 | – | V |
| Collector-Emitter Breakdown Voltage at $I_C = 1 \text{ mA}$, $I_B = 0$ | $V_{(BR)CEO}$ | 40 | – | V |
| Emitter-Base Breakdown Voltage at $I_E = 10 \mu\text{A}$, $I_C = 0$ | $V_{(BR)EBO}$ | 6.0 | – | V |
| Collector Saturation Voltage at $I_C = 10 \text{ mA}$, $I_B = 1 \text{ mA}$ at $I_C = 50 \text{ mA}$, $I_B = 5 \text{ mA}$ | V_{CEsat} V_{CEsat} | – – | 0.2 0.3 | V V |
| Base Saturation Voltage at $I_C = 10 \text{ mA}$, $I_B = 1 \text{ mA}$ at $I_C = 50 \text{ mA}$, $I_B = 5 \text{ mA}$ | V_{BEsat} V_{BEsat} | – – | 0.85 0.95 | V V |
| Collector-Emitter Cutoff Current $V_{EB} = 3 \text{ V}$, $V_{CE} = 30 \text{ V}$ | I_{CEV} | – | 50 | nA |
| Emitter-Base Cutoff Current $V_{EB} = 3 \text{ V}$, $V_{CE} = 30 \text{ V}$ | I_{EBV} | – | 50 | nA |
| DC Current Gain at $V_{CE} = 1 \text{ V}$, $I_C = 0.1 \text{ mA}$ at $V_{CE} = 1 \text{ V}$, $I_C = 1 \text{ mA}$ at $V_{CE} = 1 \text{ V}$, $I_C = 10 \text{ mA}$ at $V_{CE} = 1 \text{ V}$, $I_C = 50 \text{ mA}$ at $V_{CE} = 1 \text{ V}$, $I_C = 100 \text{ mA}$ | h_{FE} h_{FE} h_{FE} h_{FE} h_{FE} | 40 70 100 60 30 | – – 300 – – | – – – – – |
| Input Impedance at $V_{CE} = 10 \text{ V}$, $I_C = 1 \text{ mA}$, $f = 1 \text{ kHz}$ | h_{ie} | 1 | 10 | k Ω |
| Gain-Bandwidth Product at $V_{CE} = 20 \text{ V}$, $I_C = 10 \text{ mA}$, $f = 100 \text{ MHz}$ | f_T | 300 | – | MHz |
| Collector-Base Capacitance at $V_{CB} = 5 \text{ V}$, $f = 100 \text{ kHz}$ | C_{CBO} | – | 4 | pF |
| Emitter-Base Capacitance at $V_{EB} = 0.5 \text{ V}$, $f = 100 \text{ kHz}$ | C_{EBO} | – | 8 | pF |

MMBT3904

ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

| | SYMBOL | MIN. | MAX. | UNIT |
|--|----------|---------------------|-------------------|---------------|
| Voltage Feedback Ratio at $V_{CE} = 10\text{ V}$, $I_C = 1\text{ mA}$, $f = 1\text{ kHz}$ | h_{re} | $0.5 \cdot 10^{-4}$ | $8 \cdot 10^{-4}$ | – |
| Small Signal Current Gain at $V_{CE} = 10\text{ V}$, $I_C = 1\text{ mA}$, $f = 1\text{ kHz}$ | h_{fe} | 100 | 400 | – |
| Output Admittance at $V_{CE} = 1\text{ V}$, $I_C = 1\text{ mA}$, $f = 1\text{ kHz}$ | h_{oe} | 1 | 40 | μS |
| Noise Figure at $V_{CE} = 5\text{ V}$, $I_C = 100\text{ }\mu\text{A}$, $R_G = 1\text{ k}\Omega$, $f = 10 \dots 15000\text{ Hz}$ | NF | – | 5 | dB |
| Delay Time (see Fig. 1) at $I_{B1} = 1\text{ mA}$, $I_C = 10\text{ mA}$ | t_d | – | 35 | ns |
| Rise Time (see Fig. 1) at $I_{B1} = 1\text{ mA}$, $I_C = 10\text{ mA}$ | t_r | – | 35 | ns |
| Storage Time (see Fig. 2) at $-I_{B1} = I_{B2} = 1\text{ mA}$, $I_C = 10\text{ mA}$ | t_s | – | 200 | ns |
| Fall Time (see Fig. 2) at $-I_{B1} = I_{B2} = 1\text{ mA}$, $I_C = 10\text{ mA}$ | t_f | – | 50 | ns |




Fig. 1: Test circuit for delay and rise time

* total shunt capacitance of test jig and connectors





Fig. 2: Test circuit for storage and fall time

* total shunt capacitance of test jig and connectors



Layout for R_{thJA} test

Thickness: Fiberglass 0.059 in (1.5 mm)

Copper leads 0.012 in (0.3 mm)