


Line Filament Lamps

| | | Vacuum | | | | | | | | |
|-------------|-------------|--------|-------|-------|---------------|-----------|------------------|-----------------------|-----|---------|
| Line No. | Part No. | Volts | Amps | Watts | Life Hours | Or Gas | Filament Type | Filament Length, L | MOL | Drawing |
| 11 | L9050 | 3.0 | 0.360 | 1.10 | 2,000 | ٧ | S-8 | 16±1 | 36 | D |
| 12 | L9001 | 4.5 | 0.360 | 1.65 | 2,000 | V | S-8 | 23±1 | 43 | D |
| 13 | L9013 | 6.0 | 0.370 | 2.22 | 1,500 | V | S-8 | 30±1 | 50 | D |
| 14 | L9014 | 12.0 | 0.370 | 4.45 | 1,500 | V | S-8 | 60±1 | 77 | D |



Line Filament Lamps

| Line No. | Part No. | Volts | Amps | Color Temp. Degrees Kelvin | Life Hours | Vacuum Or Gas | Filament Type | Filament Length,L1 | F | Dimensions MOL | D | Drawing |
|-------------|-------------|-------|-------|----------------------------------|---------------|---------------------|------------------|-----------------------|------|-------------------|------|---------|
| 15 | L905 | 5.0 | 0.480 | 2,100 | 10,000 | V | S-8 | 38 | 8.13 | 61.0 | 4.83 | E |
| 16 | L906 | 6.0 | 0.120 | 1,990 | 12,500 | V | S-8 | 25 | 6.35 | 53.3 | 3.18 | E |
| 17 | L914 | 14.0 | 0.500 | 2,200 | 2,500 | V | S-8 | 84 | 8.13 | 119.0 | 4.83 | E |
| 18 | L918 | 18.0 | 0.120 | 1,990 | 12,500 | V | S-8 | 89 | 6.35 | 117.0 | 3.18 | E |

Telephone: 781-935-4442 Fax: 781-938-5867 Gilway Technical Lamp Engineering Catalog 169