

### STANDARD RECOVERY DIODES GEN II DO5

Stud Version

#### Features

- High surge current capability
- Designed for a wide range of applications
- Stud cathode and stud anode version
- Leaded version available/ wire version available
- Low thermal resistance
- UL approval pending

95 A

#### Typical Applications

- Battery charges
- Converters
- Power supplies
- Machine tool controls
- Welding

#### Major Ratings and Characteristics

Parameters	95PF (R)...(W)		Units
	40 to 120		
$I_{F(AV)}$		95	A
	@ $T_C$	140	°C
$I_{F(RMS)}$		149	A
$I_{FSM}$	@ 50Hz	2000	A
	@ 60Hz	2090	
$I^2t$	@ 50Hz	20000	A <sup>2</sup> s
	@ 60Hz	18180	
$V_{RRM}$	range	400 to 1200	V
$T_J$	range	- 55 to 180	°C

95PF(R)...



case style DO-203AB (DO-5)

95PF(R)...W



case style DO-203AB (DO-5)

## 95PF(R)...(W) Series

Bulletin I20208 rev. D 01/05

International  
IR Rectifier

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

Type number	Voltage Code	$V_{RRM}$ , maximum repetitive peak reverse voltage V	$V_{RSM}$ , maximum non-repetitive peak reverse voltage V	$I_{RRM}$ max. @ $T_J = 150^\circ\text{C}$ mA
95PF (R)...(W)	40	400	500	9
	80	800	960	
	120	1200	1440	

#### Forward Conduction

Parameter	95PF(R)...(W)	Units	Conditions	
	40 to 120			
$I_{F(AV)}$ Max. average forward current @ Case temperature	95	A	180° conduction, half sine wave	
	140	$^\circ\text{C}$		
$I_{F(RMS)}$ Max. RMS forward current	149	A		
$I_{FSM}$ Max. peak, one-cycle forward, non-repetitive surge current	2000	A	t = 10ms	No voltage
	2090		t = 8.3 ms	reapplied
	1680		t = 10ms	100% $V_{RRM}$
	1760		t = 8.3 ms	reapplied
$I^2t$ Maximum $I^2t$ for fusing	20000	$\text{A}^2\text{s}$	t = 10ms	No voltage
	18180		t = 8.3ms	reapplied
	14100		t = 10ms	100% $V_{RRM}$
	12800		t = 8.3ms	reapplied
$I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing	200000	$\text{A}^2\sqrt{\text{s}}$	t = 0.1 to 10ms, no voltage reapplied	
$V_{F(TO)}$ Low level value of threshold voltage	0.73	V	$(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ , $T_J = T_J \text{ max.}$	
$r_f$ Low level value of forward slope resistance	2.4	m $\Omega$	$(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ , $T_J = T_J \text{ max.}$	
$V_{FM}$ Max. forward voltage drop	1.40	V	$I_{pk} = 267\text{A}$ , $T_J = 25^\circ\text{C}$ , $t_p = 400\mu\text{s}$ rectangular wave	

Thermal and Mechanical Specifications

Parameter	95PF (R)...(W)		Units	Conditions
	40 to 120			
T <sub>J</sub> Max. junction operating temperature range	-55 to 180		°C	
T <sub>stg</sub> Max. storage temperature range	-55 to 180			
R <sub>thJC</sub> Max. thermal resistance, junction to case	0.27		K/W	DC operation
R <sub>thCS</sub> Max. thermal resistance, case to heatsink	0.25			Mounting surface, smooth, flat and greased
T Allowable mounting torque	3.4 <sup>+0-10%</sup>		Nm	Tighting on nut (1)
	30		lbf · in	Not lubricated threads
	2.3 <sup>+0-10%</sup>		Nm	Tighting on hexagon (2)
	20		lbf · in	Lubricated threads
wt Approximate weight	15.8 (0.56)		g (oz)	
Case style	DO-203AB (DO5)			See Outline Table

(1) As general recommendation we suggest to tight on Hexagon and not on nut

(2) Torque must be applicable only to Hexagon and not to plastic structure

$\Delta R_{thJC}$  Conduction

(The following table shows the increment of thermal resistance R<sub>thJC</sub> when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction	Rectangular conduction	Units	Conditions
180°	0.14	0.10	K/W	T <sub>J</sub> = T <sub>J</sub> max.
120°	0.16	0.17		
90°	0.21	0.22		
60°	0.30	0.31		
30°	0.50	0.50		




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - Forward Power Loss Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 5 - Maximum Non -Repetitive Surge Current




Fig. 6 - Maximum Non -Repetitive Surge Current




Fig. 7 - Forward Voltage Drop Characteristics





Fig. 8 - Thermal Impedance Z<sub>thJC</sub> Characteristics

Outline Table



Ordering Information Table

Device Code											
	<table border="1" style="margin: auto;"> <tr> <td style="padding: 5px;">95</td> <td style="padding: 5px;">PF</td> <td style="padding: 5px;">R</td> <td style="padding: 5px;">120</td> <td style="padding: 5px;">W</td> </tr> <tr> <td style="text-align: center;">①</td> <td style="text-align: center;">②</td> <td style="text-align: center;">③</td> <td style="text-align: center;">④</td> <td style="text-align: center;">⑤</td> </tr> </table>	95	PF	R	120	W	①	②	③	④	⑤
95	PF	R	120	W							
①	②	③	④	⑤							
<b>1</b>	<ul style="list-style-type: none"> <li>- 95 = Standard device</li> <li>- 97 = Isolated lead on standard terminal with silicone sleeve available for 1200V only (Red = Reverse Polarity) (Blue = Normal Polarity)</li> </ul>										
<b>2</b>	- PF = Plastic Package										
<b>3</b>	<ul style="list-style-type: none"> <li>- None = Stud Normal Polarity (Cathode to Stud)</li> <li>- R = Stud Reverse Polarity (Anode to Stud)</li> </ul>										
<b>4</b>	- Voltage code: Code x 10 = $V_{RRM}$ (See Voltage Ratings table)										
<b>5</b>	<ul style="list-style-type: none"> <li>- None = Standard terminal (see Fig. A)</li> <li>- W = Wire terminal (see Fig. B)</li> </ul>										

Data and specifications subject to change without notice.  
 This product has been designed and qualified for Multiple Level.  
 Qualification Standards can be found on IR's Web site.