


*Product Preview*  
**Medium Power Surface Mount Products**  
**TMOS Single P-Channel**  
**Field Effect Transistors**

WaveFET™ devices are an advanced series of power MOSFETs which utilize Motorola's High Cell Density HDTMOS process. These miniature surface mount MOSFETs feature ultra low  $R_{DS(on)}$  and true logic level performance. They are capable of withstanding high energy in the avalanche and commutation modes and the drain-to-source diode has a very low reverse recovery time. WaveFET™ devices are designed for use in low voltage, high speed switching applications where power efficiency is important. Typical applications are dc-dc converters, and power management in portable and battery powered products such as computers, printers, cellular and cordless phones. They can also be used for low voltage motor controls in mass storage products such as disk drives and tape drives. The avalanche energy is specified to eliminate the guesswork in designs where inductive loads are switched and offer additional safety margin against unexpected voltage transients.

- Ultra Low  $R_{DS(on)}$  Provides Higher Efficiency and Extends Battery Life
- Logic Level Gate Drive — Can Be Driven by Logic ICs
- Miniature SO-8 Surface Mount Package — Saves Board Space
- Diode Is Characterized for Use In Bridge Circuits
- Diode Exhibits High Speed, With Soft Recovery
- $I_{DSS}$  Specified at Elevated Temperature
- Avalanche Energy Specified
- Mounting Information for SO-8 Package Provided




**MMSF3305**

Motorola Preferred Device

**SINGLE TMOS**  
**POWER MOSFET**  
**9.1 AMPERES**  
**30 VOLTS**  
 $R_{DS(on)} = 0.02 \text{ OHM}$



**CASE 751-05, Style 13**  
**SO-8**



**DEVICE MARKING**

**ORDERING INFORMATION**

| Device | Reel Size  | Tape Width | Quantity            |            |
|--------|------------|------------|---------------------|------------|
| S3305  | MMSF3305R2 | 13"        | 12 mm embossed tape | 4000 units |

Preferred devices are Motorola recommended choices for future use and best overall value.

This document contains information on a product under development. Motorola reserves the right to change or discontinue this product without notice.

HDTMOS and WaveFET are trademarks of Motorola, Inc. TMOS is a registered trademark of Motorola, Inc.

## MMSF3305

### MAXIMUM RATINGS (T<sub>J</sub> = 25°C unless otherwise noted)

Negative sign for P-Channel devices omitted for clarity

| Rating   |  | Symbol                            | Max         | Unit  |
|--|--|-----------------------------------|-------------|-------|
| Drain-to-Source Voltage  |  | V <sub>DSS</sub>                  | 30          | V     |
| Drain-to-Gate Voltage (R <sub>GS</sub> = 1.0 MΩ)   |  | V <sub>DGR</sub>                  | 20          | V     |
| Gate-to-Source Voltage — Continuous  |  | V <sub>GS</sub>                   | ± 20        | V     |
| 1 inch SQ.<br>FR-4 or G-10 PCB<br><br>10 seconds   | Thermal Resistance — Junction to Ambient           | R <sub>THJA</sub>                 | 50          | °C/W  |
|  | Total Power Dissipation @ T <sub>A</sub> = 25°C    | P <sub>D</sub>                    | 2.5         | Watts |
|  | Linear Derating Factor                             |                                   | 20          | mW/°C |
|  | Drain Current — Continuous @ T <sub>A</sub> = 25°C | I <sub>D</sub>                    | 9.1         | A     |
|  | Continuous @ T <sub>A</sub> = 70°C                 | I <sub>D</sub>                    | 7.3         | A     |
|  | Pulsed Drain Current (1)                           | I <sub>DM</sub>                   | 50          | A     |
| Minimum<br>FR-4 or G-10 PCB<br><br>10 seconds  | Thermal Resistance — Junction to Ambient           | R <sub>THJA</sub>                 | 80          | °C/W  |
|  | Total Power Dissipation @ T <sub>A</sub> = 25°C    | P <sub>D</sub>                    | 1.56        | Watts |
|  | Linear Derating Factor                             |                                   | 12.5        | mW/°C |
|  | Drain Current — Continuous @ T <sub>A</sub> = 25°C | I <sub>D</sub>                    | 7.2         | A     |
|  | Continuous @ T <sub>A</sub> = 70°C                 | I <sub>D</sub>                    | 5.8         | A     |
|  | Pulsed Drain Current (1)                           | I <sub>DM</sub>                   | 40          | A     |
| Operating and Storage Temperature Range  |  | T <sub>J</sub> , T <sub>stg</sub> | - 55 to 150 | °C    |
| Single Pulse Drain-to-Source Avalanche Energy — Starting T <sub>J</sub> = 25°C<br>(V <sub>DD</sub> = 30 Vdc, V <sub>GS</sub> = 10 Vdc, Peak I <sub>L</sub> = 9.1 Apk, L = TBD mH, R <sub>G</sub> = 25 Ω) |  | E <sub>AS</sub>                   | TBD         | mJ    |

(1) Repetitive rating; pulse width limited by maximum junction temperature.

**ELECTRICAL CHARACTERISTICS** ( $T_C = 25^\circ\text{C}$  unless otherwise noted)

| Characteristic   | Symbol        | Min     | Typ    | Max        | Unit            |
|--|---------------|---------|--------|------------|-----------------|
| <b>OFF CHARACTERISTICS</b>   |               |         |        |            |                 |
| Drain-to-Source Breakdown Voltage<br>( $V_{GS} = 0\text{ Vdc}$ , $I_D = 0.25\text{ mAdc}$ )<br>Temperature Coefficient (Positive)  | $V_{(BR)DSS}$ | 30<br>— | —<br>— | —<br>—     | Vdc<br>mV/°C    |
| Zero Gate Voltage Drain Current<br>( $V_{DS} = 30\text{ Vdc}$ , $V_{GS} = 0\text{ Vdc}$ )<br>( $V_{DS} = 15\text{ Vdc}$ , $V_{GS} = 0\text{ Vdc}$ , $T_J = 70^\circ\text{C}$ ) | $I_{DSS}$     | —<br>—  | —<br>— | 1.0<br>5.0 | $\mu\text{Adc}$ |
| Gate-Body Leakage Current ( $V_{GS} = \pm 20\text{ Vdc}$ , $V_{DS} = 0$ )  | $I_{GSS}$     | —       | —      | 100        | nAdc            |

**ON CHARACTERISTICS(1)**

|   |              |          |        |          |              |
|---|--------------|----------|--------|----------|--------------|
| Gate Threshold Voltage<br>( $V_{DS} = V_{GS}$ , $I_D = 0.25\text{ mAdc}$ )<br>Threshold Temperature Coefficient (Negative)                              | $V_{GS(th)}$ | 0.7<br>— | —<br>— | 1.4<br>— | Vdc<br>mV/°C |
| Static Drain-to-Source On-Resistance<br>( $V_{GS} = 10\text{ Vdc}$ , $I_D = 9.1\text{ Adc}$ )<br>( $V_{GS} = 4.5\text{ Vdc}$ , $I_D = 7.3\text{ Adc}$ ) | $R_{DS(on)}$ | —<br>—   | —<br>— | 20<br>30 | m $\Omega$   |
| On-State Drain Current<br>( $V_{DS} \leq 5.0\text{ V}$ , $V_{GS} = 10\text{ V}$ )<br>( $V_{DS} \leq 5.0\text{ V}$ , $V_{GS} = 4.5\text{ V}$ )           | $I_{D(on)}$  | 40<br>10 | —<br>— | —<br>—   | A            |
| Forward Transconductance ( $V_{DS} = 15\text{ Vdc}$ , $I_D = 8.0\text{ Adc}$ )  | $g_{FS}$     | —        | —      | —        | Mhos         |

**DYNAMIC CHARACTERISTICS**

|                      |   |           |   |   |     |    |
|----------------------|---|-----------|---|---|-----|----|
| Input Capacitance    | $(V_{DS} = 30\text{ Vdc}$ , $V_{GS} = 0\text{ Vdc}$ ,<br>$f = 1.0\text{ MHz}$ ) | $C_{iss}$ | — | — | TBD | pF |
| Output Capacitance   |   | $C_{oss}$ | — | — | TBD |    |
| Transfer Capacitance |   | $C_{rss}$ | — | — | TBD |    |

**SWITCHING CHARACTERISTICS(2)**

|                             |   |              |   |   |     |    |
|-----------------------------|---|--------------|---|---|-----|----|
| Turn-On Delay Time          | $(V_{DD} = 15\text{ Vdc}$ , $I_D = 1.0\text{ Adc}$ ,<br>$V_{GS} = 10\text{ Vdc}$ ,<br>$R_G = 6.0\ \Omega$ ) (1) | $t_{d(on)}$  | — | — | TBD | ns |
| Rise Time                   |   | $t_r$        | — | — | TBD |    |
| Turn-Off Delay Time         |   | $t_{d(off)}$ | — | — | TBD |    |
| Fall Time                   |   | $t_f$        | — | — | TBD |    |
| Gate Charge<br>See Figure 8 | $(V_{DS} = 15\text{ Vdc}$ , $I_D = 4.6\text{ Adc}$ ,<br>$V_{GS} = 10\text{ Vdc}$ ) (1)                          | $Q_T$        | — | — | TBD | nC |
|                             |   | $Q_1$        | — | — | —   |    |
|                             |   | $Q_2$        | — | — | —   |    |
|                             |   | $Q_3$        | — | — | —   |    |

**SOURCE-DRAIN DIODE CHARACTERISTICS**

|  |  |          |        |        |          |     |
|--|--|----------|--------|--------|----------|-----|
| Forward On-Voltage <sup>(1)</sup>      | $(I_S = 2.1\text{ Adc}$ , $V_{GS} = 0\text{ Vdc}$ ) (1)<br>$(I_S = 2.1\text{ Adc}$ , $V_{GS} = 0\text{ Vdc}$ , $T_J = 125^\circ\text{C}$ ) | $V_{SD}$ | —<br>— | —<br>— | 1.2<br>— | Vdc |
| Reverse Recovery Time<br>See Figure 15 | $(I_S = 2.1\text{ Adc}$ , $V_{GS} = 0\text{ Vdc}$ ,<br>$di_S/dt = 100\text{ A}/\mu\text{s}$ ) (1)  | $t_{rr}$ | —      | —      | TBD      | ns  |
|  |  | $t_a$    | —      | —      | —        |     |
|  |  | $t_b$    | —      | —      | —        |     |
| Reverse Recovery Stored Charge         |  | $Q_{RR}$ | —      | —      | —        |     |

(1) Pulse Test: Pulse Width  $\leq 300\ \mu\text{s}$ , Duty Cycle  $\leq 2\%$ .


(2) Switching characteristics are independent of operating junction temperature.

(3) Reflects typical values.

$$C_{pk} = \left| \frac{\text{Max limit} - \text{Typ}}{3 \times \text{SIGMA}} \right|$$

(4) Repetitive rating; pulse width limited by maximum junction temperature.

PACKAGE DIMENSIONS



Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

Mfax is a trademark of Motorola, Inc.

**How to reach us:**

**USA/EUROPE/Locations Not Listed:** Motorola Literature Distribution; P.O. Box 5405, Denver, Colorado 80217. 303-675-2140 or 1-800-441-2447

**JAPAN:** Nippon Motorola Ltd.; Tatsumi-SPD-JLDC, 6F Seibu-Butsuryu-Center, 3-14-2 Tatsumi Koto-Ku, Tokyo 135, Japan. 81-3-3521-8315

**Mfax™:** RMFAX0@email.sps.mot.com – TOUCHTONE 602-244-6609  
– US & Canada ONLY 1-800-774-1848

**ASIA/PACIFIC:** Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park, 51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298

**INTERNET:** <http://www.mot.com/SPS/>

