


MKP3V120, MKP3V240

Preferred Device

Sidac High Voltage

Bidirectional Triggers

Bidirectional devices designed for direct interface with the ac power line. Upon reaching the breakover voltage in each direction, the device switches from a blocking state to a low voltage on-state. Conduction will continue like a Triac until the main terminal current drops below the holding current. The plastic axial lead package provides high pulse current capability at low cost. Glass passivation insures reliable operation. Applications are:

- High Pressure Sodium Vapor Lighting
- Strobes and Flashers
- Ignitors
- High Voltage Regulators
- Pulse Generators
- Used to Trigger Gates of SCR's and Triacs
-  Indicates UL Registered — File #E116110
- Device Marking: Logo, Device Type, e.g., MKP3V120, Date Code

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Peak Repetitive Off-State Voltage (Sine Wave, 50 to 60 Hz, T _J = -40 to 125°C) MKP3V120 MKP3V240	V _{DRM} , V _R RM	±90 ±180	Volts
On-State RMS Current (T _L = 80°C, Lead Length = 3/8", All Conduction Angles)	I _{T(RMS)}	±1.0	Amp
Peak Non-Repetitive Surge Current (60 Hz One Cycle Sine Wave, Peak Value, T _J = 125°C)	I _{TSM}	±20	Amps
Operating Junction Temperature Range	T _J	-40 to +125	°C
Storage Temperature Range	T _{stg}	-40 to +150	°C



ON Semiconductor

<http://onsemi.com>

SIDACS (∞)
1 AMPERE RMS
120 and 240 VOLTS



SURMETIC 50
PLASTIC AXIAL
(No Polarity)
CASE 267
STYLE 2

ORDERING INFORMATION

Device	Package	Shipping
MKP3V120	SURMETIC 50	Bulk 500/Bag
MKP3V120RL	SURMETIC 50	Tape and Reel 1.5K/Reel
MKP3V240	SURMETIC 50	Bulk 500/Bag
MKP3V240RL	SURMETIC 50	Tape and Reel 1.5K/Reel

Preferred devices are recommended choices for future use and best overall value.

MKP3V120, MKP3V240

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Lead (Lead Length = 3/8")	$R_{\theta JL}$	15	$^{\circ}C/W$
Lead Solder Temperature (Lead Length \geq 1/16" from Case, 10 s Max)	T_L	260	$^{\circ}C$

ELECTRICAL CHARACTERISTICS ($T_C = 25^{\circ}C$ unless otherwise noted; Electricals apply in both directions)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS

Repetitive Peak Off-State Current (50 to 60 Hz Sine Wave) $V_{DRM} = 90 V$ $V_{DRM} = 180 V$	I_{DRM}	—	—	10	μA
					MKP3V120 MKP3V240

ON CHARACTERISTICS

Breakover Voltage, $I_{BO} = 200 \mu A$	V_{BO}	110 220	— —	130 250	Volts
					MKP3V120 MKP3V240
Breakover Current	I_{BO}	—	—	200	μA
Peak On-State Voltage ($I_{TM} = 1 A$ Peak, Pulse Width $\leq 300 \mu s$, Duty Cycle $\leq 2\%$)	V_{TM}	—	1.1	1.5	Volts
Dynamic Holding Current (Sine Wave, 60 Hz, $R_L = 100 \Omega$)	I_H	—	—	100	mA
Switching Resistance (Sine Wave, 50 to 60 Hz)	R_S	0.1	—	—	$k\Omega$


DYNAMIC CHARACTERISTICS

Critical Rate-of-Rise of On-State Current, Critical Damped Waveform Circuit ($I_{PK} = 130 A$ Amps, Pulse Width = 10 μsec)	di/dt	—	120	—	$A/\mu s$
---	---------	---	-----	---	-----------

MKP3V120, MKP3V240

Voltage Current Characteristic of SIDAC (Bidirectional Device)

Symbol	Parameter
I_{DRM}	Off State Leakage Current
V_{DRM}	Off State Repetitive Blocking Voltage
V_{BO}	Breakover Voltage
I_{BO}	Breakover Current
I_H	Holding Current
V_{TM}	On State Voltage
I_{TM}	Peak on State Current



CURRENT DERATING




Figure 1. Maximum Case Temperature




Figure 2. Maximum Ambient Temperature




Figure 3. Typical Forward Voltage




Figure 4. Typical Power Dissipation

MKP3V120, MKP3V240

THERMAL CHARACTERISTICS




Figure 5. Thermal Response

TYPICAL CHARACTERISTICS




Figure 6. Typical Breakover Current





Figure 7. Typical Holding Current

MKP3V120, MKP3V240

PACKAGE DIMENSIONS

SURMETIC 50
PLASTIC AXIAL
(No Polarity)
CASE 267-03
ISSUE D



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.370	0.380	9.40	9.65
B	0.190	0.210	4.83	5.33
D	0.048	0.052	1.22	1.32
K	1.000	---	25.40	---

STYLE 2:

NO POLARITY

Notes

Notes

MKP3V120, MKP3V240

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

NORTH AMERICA Literature Fulfillment:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com
Fax Response Line: 303-675-2167 or 800-344-3810 Toll Free USA/Canada

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

EUROPE: LDC for ON Semiconductor – European Support

German Phone: (+1) 303-308-7140 (M-F 1:00pm to 5:00pm Munich Time)
Email: ONlit-german@hibbertco.com
French Phone: (+1) 303-308-7141 (M-F 1:00pm to 5:00pm Toulouse Time)
Email: ONlit-french@hibbertco.com
English Phone: (+1) 303-308-7142 (M-F 12:00pm to 5:00pm UK Time)
Email: ONlit@hibbertco.com

EUROPEAN TOLL-FREE ACCESS*: 00-800-4422-3781

*Available from Germany, France, Italy, England, Ireland

CENTRAL/SOUTH AMERICA:

Spanish Phone: 303-308-7143 (Mon-Fri 8:00am to 5:00pm MST)
Email: ONlit-spanish@hibbertco.com

ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support

Phone: 303-675-2121 (Tue-Fri 9:00am to 1:00pm, Hong Kong Time)
Toll Free from Hong Kong & Singapore:
001-800-4422-3781
Email: ONlit-asia@hibbertco.com

JAPAN: ON Semiconductor, Japan Customer Focus Center
4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031

Phone: 81-3-5740-2745
Email: r14525@onsemi.com

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local Sales Representative.