

**Document Title****256Kx8 bit Low Power and Low Voltage CMOS Static RAM****Revision History**

| <b><u>Revision No.</u></b> | <b><u>History</u></b>  | <b><u>Draft Data</u></b> | <b><u>Remark</u></b> |
|----------------------------|--|--------------------------|----------------------|
| 0.0                        | Design target  | January 30, 1997         | Advance              |
| 0.1                        | Initial draft  | April 7, 1997            | Preliminary          |
| 1.0                        | Finalize<br>- Improved $V_{IL}(\text{Min.})$ : 0.4V → 0.6V<br>- Erase reverse type package<br>- Change speed bin<br>KM68V2000 : 70/85ns<br>KM68V2000I, KM68U2000, KM68U2000I : 85/100ns<br>- Improved standby current<br>Commercial product : 15 $\mu$ A → 10 $\mu$ A<br>Industrial product : 30 $\mu$ A → 15 $\mu$ A<br>- Increased Power dissipation : 0.7W → 1.0W | November 27, 1997        | Final                |

---

The attached datasheets are provided by SAMSUNG Electronics. SAMSUNG Electronics CO., LTD. reserve the right to change the specifications and products. SAMSUNG Electronics will answer to your questions. If you have any questions, please contact the SAMSUNG branch offices.

---

## 256Kx8 bit Low Power and Low Voltage CMOS Static RAM

### FEATURES

- Process Technology: TFT
- Organization: 256Kx8
- Power Supply Voltage  
K6T2008V2M Family: 3.0V ~ 3.6V  
K6T2008U2M Family: 2.7V ~ 3.3V
- Low Data Retention Voltage: 2V(Min)
- Three state output and TTL Compatible
- Package Type: 32-TSOP1-0820F, 32-TSOP1-0813.4F

### GENERAL DESCRIPTION


The K6T2008V2M and K6T2008U2M families are fabricated by SAMSUNG's advanced CMOS process technology. The families support various operating temperature ranges and have various package types for user flexibility of system design. The families also support low data retention voltage for battery back-up operation with low data retention current.

### PRODUCT FAMILY

| Product Family               | Operating Temperature    | Vcc Range            | Speed                | Power Dissipation                |                                    | PKG Type                  |
|------------------------------|--------------------------|----------------------|----------------------|----------------------------------|------------------------------------|---------------------------|
|                              |                          |                      |                      | Standby (I <sub>SB1</sub> , Max) | Operating (I <sub>CC2</sub> , Max) |                           |
| K6T2008V2M-B<br>K6T2008U2M-B | Commercial<br>(0~70°C)   | 3.0~3.6V<br>2.7~3.3V | 70/85ns<br>85/100ns  | 10µA                             | 40mA <sup>1)</sup>                 | 32-TSOP1-F<br>32-sTSOP1-F |
| K6T2008V2M-F<br>K6T2008U2M-F | Industrial<br>(-40~85°C) | 3.0~3.6V<br>2.7~3.3V | 85/100ns<br>85/100ns | 15µA                             |                                    |                           |


1. K6T2008V2M family = 50mA

### PIN DESCRIPTION



| Name                               | Function            |
|------------------------------------|---------------------|
| $\overline{CS}_1, \overline{CS}_2$ | Chip Select Input   |
| $\overline{OE}$                    | Output Enable Input |
| $\overline{WE}$                    | Write Enable Input  |
| A0~A17                             | Address Inputs      |
| I/O1~I/O8                          | Data Inputs/Outputs |
| Vcc                                | Power               |
| Vss                                | Ground              |
| N.C.                               | No Connection       |

### FUNCTIONAL BLOCK DIAGRAM



SAMSUNG ELECTRONICS CO., LTD. reserves the right to change products and specifications without notice.

## PRODUCT LIST

| Commercial Temperature Products(0~70°C) |   | Industrial Temperature Products(-40~85°C) |   |
|---|---|---|---|
| Part Name                               | Function  | Part Name                                 | Function  |
| K6T2008V2M-TB70<br>K6T2008V2M-TB85      | 32-TSOP1 F, 70ns, 3.3V, LL<br>32-TSOP1 F, 85ns, 3.3V, LL    | K6T2008V2M-TF85<br>K6T2008V2M-TF10        | 32-TSOP1 F, 85ns, 3.3V, LL<br>32-TSOP1 F, 100ns, 3.3V, LL   |
| K6T2008U2M-TB85<br>K6T2008U2M-TB10      | 32-TSOP1 F, 85ns, 3.0V, LL<br>32-TSOP1 F, 100ns, 3.0V, LL   | K6T2008U2M-TF85<br>K6T2008U2M-TF10        | 32-TSOP1 F, 85ns, 3.0V, LL<br>32-TSOP1 F, 100ns, 3.0V, LL   |
| K6T2008V2M-YB70<br>K6T2008V2M-YB85      | 32-sTSOP1 F, 70ns, 3.3V,LL<br>32-sTSOP1 F, 85ns, 3.3V,LL    | K6T2008V2M-YF85<br>K6T2008V2M-YF10        | 32-sTSOP1 F, 85ns, 3.3V,LL<br>32-sTSOP1 F, 100ns, 3.3V,LL   |
| K6T2008U2M-YB85<br>K6T2008U2M-YB10      | 32-sTSOP1 F, 85ns, 3.0V, LL<br>32-sTSOP1 F, 100ns, 3.0V, LL | K6T2008U2M-YF85<br>K6T2008U2M-YF10        | 32-sTSOP1 F, 85ns, 3.0V, LL<br>32-sTSOP1 F, 100ns, 3.0V, LL |

## FUNCTIONAL DESCRIPTION

| CS <sub>1</sub> | CS <sub>2</sub> | OE              | WE              | I/O    | Mode            | Power   |
|-----------------|-----------------|-----------------|-----------------|--------|-----------------|---------|
| H               | X <sup>1)</sup> | X <sup>1)</sup> | X <sup>1)</sup> | High-Z | Deselected      | Standby |
| X <sup>1)</sup> | L               | X <sup>1)</sup> | X <sup>1)</sup> | High-Z | Deselected      | Standby |
| L               | H               | H               | H               | High-Z | Output Disabled | Active  |
| L               | H               | L               | H               | Dout   | Read            | Active  |
| L               | H               | X <sup>1)</sup> | L               | Din    | Write           | Active  |

1. X means don't care (Must be in high or low states)

## ABSOLUTE MAXIMUM RATINGS<sup>1)</sup>

| Item  | Symbol                            | Ratings                      | Unit | Remark                     |
|---|-----------------------------------|------------------------------|------|----------------------------|
| Voltage on any pin relative to V <sub>SS</sub>                | V <sub>IN</sub> ,V <sub>OUT</sub> | -0.5 to V <sub>CC</sub> +0.5 | V    | -                          |
| Voltage on V <sub>CC</sub> supply relative to V <sub>SS</sub> | V <sub>CC</sub>                   | -0.3 to 4.6                  | V    | -                          |
| Power Dissipation   | P <sub>D</sub>                    | 1.0                          | W    | -                          |
| Storage temperature   | T <sub>STG</sub>                  | -65 to 150                   | °C   | -                          |
| Operating Temperature   | T <sub>A</sub>                    | 0 to 70                      | °C   | K6T2008V2M-L, K6T2008U2M-L |
|   |                                   | -40 to 85                    | °C   | K6T2008V2M-P, K6T2008U2M-P |
| Soldering temperature and time                                | T <sub>SOLDER</sub>               | 260°C, 10sec(Lead Only)      | -    | -                          |

1. Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. Functional operation should be restricted to recommended operating condition. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

RECOMMENDED DC OPERATING CONDITIONS<sup>1)</sup>

| Item               | Symbol          | Product                                | Min                | Typ        | Max                                | Unit |
|--------------------|-----------------|--|--------------------|------------|------------------------------------|------|
| Supply voltage     | V <sub>CC</sub> | K6T2008V2M Family<br>K6T2008U2M Family | 3.0<br>2.7         | 3.3<br>3.0 | 3.6<br>3.3                         | V    |
| Ground             | V <sub>SS</sub> | All Family                             | 0                  | 0          | 0                                  | V    |
| Input high voltage | V <sub>IH</sub> | K6T2008V2M, K6T2008U2M Family          | 2.2                | -          | V <sub>CC</sub> +0.3 <sup>2)</sup> | V    |
| Input low voltage  | V <sub>IL</sub> | K6T2008V2M, K6T2008U2M Family          | -0.3 <sup>3)</sup> | -          | 0.6                                | V    |

Note:

- Commercial Product : T<sub>A</sub>=0 to 70°C, otherwise specified  
Industrial Product : T<sub>A</sub>=-40 to 85°C, otherwise specified
- Overshoot : V<sub>CC</sub>+3.0V in case of pulse width≤30ns
- Undershoot : -3.0V in case of pulse width≤30ns
- Overshoot and undershoot are sampled, not 100% tested.

CAPACITANCE<sup>1)</sup> (f=1MHz, T<sub>A</sub>=25°C)

| Item                     | Symbol          | Test Condition      | Min | Max | Unit |
|--------------------------|-----------------|---------------------|-----|-----|------|
| Input capacitance        | C <sub>IN</sub> | V <sub>IN</sub> =0V | -   | 8   | pF   |
| Input/Output capacitance | C <sub>IO</sub> | V <sub>IO</sub> =0V | -   | 10  | pF   |

- Capacitance is sampled, not 100% tested

## DC AND OPERATING CHARACTERISTICS


| Item                      | Symbol           | Test Conditions  | Min   | Typ | Max              | Unit |    |
|---------------------------|------------------|--|-------|-----|------------------|------|----|
| Input leakage current     | I <sub>LI</sub>  | V <sub>IN</sub> =V <sub>SS</sub> to V <sub>CC</sub>  | -1    | -   | 1                | μA   |    |
| Output leakage current    | I <sub>LO</sub>  | $\overline{CS}_1=V_{IH}$ or $CS_2=V_{IL}$ or $\overline{OE}=V_{IH}$ or $\overline{WE}=V_{IL}$ , V <sub>IO</sub> =V <sub>SS</sub> to V <sub>CC</sub>                                    | -1    | -   | 1                | μA   |    |
| Operating power supply    | I <sub>CC</sub>  | I <sub>IO</sub> =0mA, $\overline{CS}_1=V_{IL}$ , CS <sub>2</sub> =V <sub>IH</sub> , V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub> , Read   | -     | 2   | 5                | mA   |    |
| Average operating current | I <sub>CC1</sub> | Cycle time=1μs, 100% duty, I <sub>IO</sub> =0mA, $\overline{CS}_1 \leq 0.2V$ , CS <sub>2</sub> ≥V <sub>CC</sub> -0.2V, V <sub>IN</sub> ≤0.2V or V <sub>IN</sub> ≥V <sub>CC</sub> -0.2V | Read  | -   | 2                | 5    | mA |
|                           |                  |  | Write | -   | 10               | 15   |    |
|                           | I <sub>CC2</sub> | Cycle time=Min, 100% duty, I <sub>IO</sub> =0mA, $\overline{CS}_1=V_{IL}$ , CS <sub>2</sub> =V <sub>IH</sub> , V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub>                     | -     | 30  | 40 <sup>1)</sup> | mA   |    |
| Output low voltage        | V <sub>OL</sub>  | I <sub>OL</sub> =2.1mA   | -     | -   | 0.4              | V    |    |
| Output high voltage       | V <sub>OH</sub>  | I <sub>OH</sub> =-1.0mA  | 2.2   | -   | -                | V    |    |
| Standby Current(TTL)      | I <sub>SB</sub>  | $\overline{CS}_1=V_{IH}$ , CS <sub>2</sub> =V <sub>IL</sub> , Other inputs=V <sub>IH</sub> or V <sub>IL</sub>  | -     | -   | 0.3              | mA   |    |
| Standby Current(CMOS)     | I <sub>SB1</sub> | $\overline{CS}_1 \geq V_{CC}-0.2V$ , CS <sub>2</sub> ≥V <sub>CC</sub> -0.2V or CS <sub>2</sub> ≤0.2V, Other inputs=0-V <sub>CC</sub>   | -     | 0.2 | 10 <sup>2)</sup> | μA   |    |

- K6T2008V2M Family = 50mA
- Industrial product = 15μA

## AC OPERATING CONDITIONS

### TEST CONDITIONS (Test Load and Input/Output Reference)

Input pulse level: 0.4 to 2.2V  
 Input rising and falling time: 5ns  
 Input and output reference voltage: 1.5V  
 Output load (see right):  $CL=100pF+1TTL$



1. Including scope and jig capacitance

## AC CHARACTERISTICS (K6T2008V2M Family: $V_{CC}=3.0\sim 3.6V$ , K6T2008U2M Family: $V_{CC}=2.7\sim 3.3V$ Commercial Product: $T_A=0$ to $70^\circ C$ , Industrial Product: $T_A=-40$ to $85^\circ C$ )

| Parameter List |                                 | Symbol                              | Speed Bins |     |      |     |       |     | Units |
|----------------|---------------------------------|-------------------------------------|------------|-----|------|-----|-------|-----|-------|
|                |                                 |                                     | 70ns       |     | 85ns |     | 100ns |     |       |
|                |                                 |                                     | Min        | Max | Min  | Max | Min   | Max |       |
| Read           | Read cycle time                 | t <sub>RC</sub>                     | 70         | -   | 85   | -   | 100   | -   | ns    |
|                | Address access time             | t <sub>AA</sub>                     | -          | 70  | -    | 85  | -     | 100 | ns    |
|                | Chip select to output           | t <sub>CO1</sub> , t <sub>CO2</sub> | -          | 70  | -    | 85  | -     | 100 | ns    |
|                | Output enable to valid output   | t <sub>OE</sub>                     | -          | 35  | -    | 40  | -     | 50  | ns    |
|                | Chip select to low-Z output     | t <sub>LZ</sub>                     | 10         | -   | 10   | -   | 10    | -   | ns    |
|                | Output enable to low-Z output   | t <sub>OLZ</sub>                    | 5          | -   | 5    | -   | 5     | -   | ns    |
|                | Chip disable to high-Z output   | t <sub>HZ</sub>                     | 0          | 25  | 0    | 25  | 0     | 30  | ns    |
|                | Output disable to high-Z output | t <sub>OHZ</sub>                    | 0          | 25  | 0    | 25  | 0     | 30  | ns    |
|                | Output hold from address change | t <sub>OH</sub>                     | 10         | -   | 15   | -   | 15    | -   | ns    |
| Write          | Write cycle time                | t <sub>WC</sub>                     | 70         | -   | 85   | -   | 100   | -   | ns    |
|                | Chip select to end of write     | t <sub>CW</sub>                     | 60         | -   | 70   | -   | 80    | -   | ns    |
|                | Address set-up time             | t <sub>AS</sub>                     | 0          | -   | 0    | -   | 0     | -   | ns    |
|                | Address valid to end of write   | t <sub>AW</sub>                     | 60         | -   | 70   | -   | 80    | -   | ns    |
|                | Write pulse width               | t <sub>WP</sub>                     | 55         | -   | 60   | -   | 70    | -   | ns    |
|                | Write recovery time             | t <sub>WR</sub>                     | 0          | -   | 0    | -   | 0     | -   | ns    |
|                | Write to output high-Z          | t <sub>WHZ</sub>                    | 0          | 25  | 0    | 30  | 0     | 30  | ns    |
|                | Data to write time overlap      | t <sub>DW</sub>                     | 30         | -   | 35   | -   | 40    | -   | ns    |
|                | Data hold from write time       | t <sub>DH</sub>                     | 0          | -   | 0    | -   | 0     | -   | ns    |
|                | End write to output low-Z       | t <sub>OW</sub>                     | 5          | -   | 5    | -   | 5     | -   | ns    |


## DATA RETENTION CHARACTERISTICS

| Item                               | Symbol           |                          | Test Condition  | Min | Typ | Max      | Unit    |
|------------------------------------|------------------|--------------------------|---|-----|-----|----------|---------|
| V <sub>CC</sub> for data retention | V <sub>DR</sub>  |                          | $\overline{CS}_1^{(1)} \geq V_{CC}-0.2V$  | 2.0 | -   | 3.6      | V       |
| Data retention current             | I <sub>DR</sub>  | Commercial<br>Industrial | $V_{CC}=3.0V$ $\overline{CS}_1 \geq V_{CC}-0.2V$<br>$CS_2 \geq V_{CC}-0.2V$ or $CS_2 \leq 0.2V$ |     | 0.2 | 10<br>15 | $\mu A$ |
| Data retention set-up time         | t <sub>SDR</sub> |                          | See data retention waveform   | 0   | -   | -        | ms      |
| Recovery time                      | t <sub>RDR</sub> |                          |   | 5   | -   | -        |         |


1.  $\overline{CS}_1 \geq V_{CC}-0.2V$ ,  $CS_2 \geq V_{CC}-0.2V$  ( $\overline{CS}_1$  controlled) or  $CS_2 \leq 0.2V$  ( $CS_2$  controlled)

## TIMMING DIAGRAMS

**TIMING WAVEFORM OF READ CYCLE(1)** (Address Controlled,  $\overline{CS}_1 = \overline{OE} = V_{IL}$ ,  $\overline{WE} = V_{IH}$ )




**TIMING WAVEFORM OF READ CYCLE(2)** ( $\overline{WE} = V_{IH}$ )




**NOTES (READ CYCLE)**

1.  $t_{HZ}$  and  $t_{OHZ}$  are defined as the time at which the outputs achieve the open circuit conditions and are not referenced to output voltage levels.
2. At any given temperature and voltage condition,  $t_{HZ}(\text{Max.})$  is less than  $t_{LZ}(\text{Min.})$  both for a given device and from device to device interconnection.

TIMING WAVEFORM OF WRITE CYCLE(1) ( $\overline{WE}$  Controlled)



TIMING WAVEFORM OF WRITE CYCLE(2) ( $\overline{CS1}$  Controlled)



## TIMING WAVEFORM OF WRITE CYCLE(3) (CS<sub>2</sub> Controlled)




### NOTES (WRITE CYCLE)


1. A write occurs during the overlap of a low  $\overline{CS}_1$ , a high  $CS_2$  and a low  $\overline{WE}$ . A write begins at the latest transition among  $\overline{CS}_1$  goes low,  $CS_2$  going high and  $\overline{WE}$  going low : A write ends at the earliest transition among  $CS_1$  going high,  $CS_2$  going low and  $\overline{WE}$  going high,  $t_{WP}$  is measured from the beginning of write to the end of write.
2.  $t_{CW}$  is measured from the  $\overline{CS}_1$  going low or  $CS_2$  going high to the end of write.
3.  $t_{AS}$  is measured from the address valid to the beginning of write.
4.  $t_{WR}$  is measured from the end of write to the address change.  $t_{WR1}$  applied in case a write ends as  $\overline{CS}_1$  or  $\overline{WE}$  going high  $t_{WR2}$  applied in case a write ends as  $CS_2$  going to low.

## DATA RETENTION WAVE FORM

### $\overline{CS}_1$ controlled



### $CS_2$ controlled




1. 3.0V for K6T2008V2M Family, 2.7V for K6T2008U2M Family.



## PACKAGE DIMENSIONS

Units: millimeters(inches)

### 32 PIN THIN SMALL OUTLINE PACKAGE TYPE I (0820F)



### 32 PIN SMALLER THIN SMALL OUTLINE PACKAGE TYPE I (0813.4F)

