

2SK1712

External dimensions 1 FM20

Absolute Maximum Ratings (Ta = 25°C)

Symbol	Ratings	Unit
V _{DSS}	60	V
V _{GSS}	±10	V
I _D	±15	A
I _D (pulse)	±60 (T _{ch} ≤ 150°C)	A
P _D	30 (T _c = 25°C)	W
E _{AS} *	6.2	mJ
T _{ch}	150	°C
T _{stg}	-55 to +150	°C

*: V_{DD} = 25V, L = 50μH, I_L = 12A, unclamped, See Figure 1 on Page 5.

Electrical Characteristics (Ta = 25°C)

Symbol	Ratings			Unit	Conditions
	min	typ	max		
V _{(BR) DSS}	60			V	I _D = 250μA, V _{GS} = 0V
I _{GSS}			±500	nA	V _{GS} = ±10V
I _{bSS}			250	μA	V _{DS} = 60V, V _{GS} = 0V
V _{TH}	1.0		2.0	V	V _{DS} = 10V, I _D = 250μA
Re (yfs)	5.6	8.4		S	V _{DS} = 10V, I _D = 8.0A
R _{DS} (on)		0.12	0.14	Ω	V _{GS} = 4V, I _D = 8.0A
		0.07	0.1	Ω	V _{GS} = 10V, I _D = 8.0A
C _{iss}		820		pF	V _{DS} = 25V, f = 1.0MHz, V _{GS} = 0V
C _{oss}		360		pF	
t _{on}		100		ns	I _D = 8A, V _{DD} = 30V, V _{GS} = 10V, See Figure 2 on Page 5.
t _{off}		75		ns	

