

NPN TRANSISTOR**8050****1.5A**

- Power Dissipation
Pcm : 1.0W
- Collector Current
Icm : 1.5A
- Collector-Base Voltage
Vcbo: 45V

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (Ta=25)

PARAMETERS	SYMBOL	MIN	TYP	MAX	UNIT	CONDITION
Collector-Emitter Breakdown Voltage	BVceo	25			V	Ic=0.1mA
Collector-Base Breakdown Voltage	BVcbo	45			V	Ic=100µA
Emitter-Base Breakdown Voltage	BVebo	5			V	Ie=100 µ A
Collector-Base Leakage	Icbo			0.1	µA	Vcb=40V
Collector-Emitter Leakage	Iceo			0.1	µA	Vce=20V
Emitter-Base Leakage	Iebo			0.1	µA	Veb=5V
Collector-Emitter Saturation Voltage	Vce(sat)			0.6	V	Ic=1500mA, Ib=50mA
Base-Emiiter Saturation Voltage	Vbe(sat)			1.2	V	Ic=1500mA, Ib=50mA
DC Current Gain	Hfe1 Hfe2	85 50		300		Vce=1V,Ic=50mA Vce=1V,Ic=500mA
Collector Current	Ic			1.5	A	
Peak Collector Current	Icp			8	A(Pulse)	
Current Gain Bandwidth	fT	150			MHz	Vcb=6V, Ic=20mA
Output Capacitance	Cob			32	pF	Vcb=20V,Ie=0,f=1MHz
Power Dissipation	Pc			1.0	W	
Junction Temperature	Tj			150		
Storage Temperature	Tstg	-55		150		

Hfe1 Classification

Rank	B	C	D
Range	85-160	120-200	160-300

**STANSON TECHNOLOGY**

120 Bentley Square, Mountain View, Ca 94040 USA

TEL: (650) 9389294 FAX: (650) 9389295