



# STP36NF06 STP36NF06FP

N-CHANNEL 60V - 0.032  $\Omega$  - 30A TO-220/TO-220FP  
STripFET™ II POWER MOSFET

| TYPE        | V <sub>DSS</sub> | R <sub>DS(on)</sub> | I <sub>D</sub> |
|-------------|------------------|---------------------|----------------|
| STP36NF06   | 60 V             | <0.040 $\Omega$     | 30 A           |
| STP36NF06FP | 60 V             | <0.040 $\Omega$     | 18 A(*)        |


- TYPICAL R<sub>DS(on)</sub> = 0.032  $\Omega$
- EXCEPTIONAL dv/dt CAPABILITY
- 100% AVALANCHE TESTED
- APPLICATION ORIENTED CHARACTERIZATION

## DESCRIPTION


This Power MOSFET is the latest development of STMicroelectronics unique "Single Feature Size™" strip-based process. The resulting transistor shows extremely high packing density for low on-resistance, rugged avalanche characteristics and less critical alignment steps therefore a remarkable manufacturing reproducibility.

## APPLICATIONS

- HIGH CURRENT, HIGH SWITCHING SPEED



## INTERNAL SCHEMATIC DIAGRAM



## Ordering Information

| SALES TYPE  | MARKING     | PACKAGE  | PACKAGING |
|-------------|-------------|----------|-----------|
| STP36NF06   | STP36NF06   | TO-220   | TUBE      |
| STP36NF06FP | STP36NF06FP | TO-220FP | TUBE      |

## ABSOLUTE MAXIMUM RATINGS

| Symbol              | Parameter   | Value      |             | Unit |
|---------------------|---|------------|-------------|------|
|                     |   | STP36NF06  | STP36NF06FP |      |
| V <sub>DS</sub>     | Drain-source Voltage (V <sub>GS</sub> = 0)            | 60         |             | V    |
| V <sub>DGR</sub>    | Drain-gate Voltage (R <sub>GS</sub> = 20 k $\Omega$ ) | 60         |             | V    |
| V <sub>GS</sub>     | Gate- source Voltage                                  | $\pm 20$   |             | V    |
| I <sub>D</sub>      | Drain Current (continuous) at T <sub>C</sub> = 25°C   | 30         | 18(*)       | A    |
| I <sub>D</sub>      | Drain Current (continuous) at T <sub>C</sub> = 100°C  | 21         | 12          | A    |
| I <sub>DM</sub> (•) | Drain Current (pulsed)                                | 120        | 72          | A    |
| P <sub>tot</sub>    | Total Dissipation at T <sub>C</sub> = 25°C            | 70         | 25          | W    |
|                     | Derating Factor                                       | 0.47       | 0.17        | W/°C |
| dv/dt (1)           | Peak Diode Recovery voltage slope                     | 20         |             | V/ns |
| E <sub>AS</sub> (2) | Single Pulse Avalanche Energy                         | 200        |             | mJ   |
| T <sub>stg</sub>    | Storage Temperature                                   | -55 to 175 |             | °C   |
| T <sub>j</sub>      | Max. Operating Junction Temperature                   |            |             |      |

(•) Pulse width limited by safe operating area.

(\*) Current Limited by Package

(1) I<sub>SD</sub>  $\leq$  36A, di/dt  $\leq$  400A/ $\mu$ s, V<sub>DD</sub>  $\leq$  V<sub>(BR)DSS</sub>, T<sub>j</sub>  $\leq$  T<sub>JMAX</sub>

(2) Starting T<sub>j</sub> = 25 °C, I<sub>D</sub> = 18 A, V<sub>DD</sub> = 45V

**THERMAL DATA**

|                |  |     | TO-220 | TO-220FP |      |
|----------------|--|-----|--------|----------|------|
| Rthj-case      | Thermal Resistance Junction-case   | Max | 2.14   | 6        | °C/W |
| Rthj-amb       | Thermal Resistance Junction-ambient  | Max | 62.5   |          | °C/W |
| T <sub>l</sub> | Maximum Lead Temperature For Soldering Purpose<br>(1.6 mm from case, for 10 sec) |     | 300    |          |      |

**ELECTRICAL CHARACTERISTICS** (T<sub>case</sub> = 25 °C unless otherwise specified)

**OFF**

| Symbol               | Parameter   | Test Conditions   | Min. | Typ. | Max.    | Unit     |
|----------------------|---|---|------|------|---------|----------|
| V <sub>(BR)DSS</sub> | Drain-source Breakdown Voltage                        | I <sub>D</sub> = 250 μA, V <sub>GS</sub> = 0  | 60   |      |         | V        |
| I <sub>DSS</sub>     | Zero Gate Voltage Drain Current (V <sub>GS</sub> = 0) | V <sub>DS</sub> = Max Rating<br>V <sub>DS</sub> = Max Rating T <sub>C</sub> = 125°C |      |      | 1<br>10 | μA<br>μA |
| I <sub>GSS</sub>     | Gate-body Leakage Current (V <sub>DS</sub> = 0)       | V <sub>GS</sub> = ± 20 V  |      |      | ±100    | nA       |

**ON (\*)**

| Symbol              | Parameter                         | Test Conditions   | Min. | Typ.  | Max.  | Unit |
|---------------------|-----------------------------------|---|------|-------|-------|------|
| V <sub>GS(th)</sub> | Gate Threshold Voltage            | V <sub>DS</sub> = V <sub>GS</sub> I <sub>D</sub> = 250 μA | 2    |       |       | V    |
| R <sub>DS(on)</sub> | Static Drain-source On Resistance | V <sub>GS</sub> = 10 V I <sub>D</sub> = 15 A              |      | 0.032 | 0.040 | Ω    |

**DYNAMIC**

| Symbol              | Parameter                    | Test Conditions                                     | Min. | Typ. | Max. | Unit |
|---------------------|------------------------------|---|------|------|------|------|
| g <sub>fs</sub> (*) | Forward Transconductance     | V <sub>DS</sub> = 25 V I <sub>D</sub> = 15 A        |      | 12   |      | S    |
| C <sub>iss</sub>    | Input Capacitance            | V <sub>DS</sub> = 25V f = 1 MHz V <sub>GS</sub> = 0 |      | 690  |      | pF   |
| C <sub>oss</sub>    | Output Capacitance           |   |      | 170  |      | pF   |
| C <sub>rss</sub>    | Reverse Transfer Capacitance |   |      | 68   |      | pF   |

**ELECTRICAL CHARACTERISTICS** (continued)

**SWITCHING ON**

| Symbol                        | Parameter  | Test Conditions  | Min. | Typ.         | Max. | Unit           |
|-------------------------------|--|--|------|--------------|------|----------------|
| $t_{d(on)}$<br>$t_r$          | Turn-on Delay Time<br>Rise Time                              | $V_{DD} = 30\text{ V}$ $I_D = 18\text{ A}$<br>$R_G = 4.7\ \Omega$ $V_{GS} = 10\text{ V}$<br>(Resistive Load, Figure 3) |      | 10<br>40     |      | ns<br>ns       |
| $Q_g$<br>$Q_{gs}$<br>$Q_{gd}$ | Total Gate Charge<br>Gate-Source Charge<br>Gate-Drain Charge | $V_{DD} = 30\text{ V}$ $I_D = 36\text{ A}$ $V_{GS} = 10\text{ V}$  |      | 23<br>6<br>9 | 31   | nC<br>nC<br>nC |

**SWITCHING OFF**


| Symbol                | Parameter                        | Test Conditions  | Min. | Typ.    | Max. | Unit     |
|-----------------------|----------------------------------|--|------|---------|------|----------|
| $t_{d(off)}$<br>$t_f$ | Turn-off Delay Time<br>Fall Time | $V_{DD} = 30\text{ V}$ $I_D = 18\text{ A}$<br>$R_G = 4.7\ \Omega$ $V_{GS} = 10\text{ V}$<br>(Resistive Load, Figure 3) |      | 27<br>9 |      | ns<br>ns |

**SOURCE DRAIN DIODE**


| Symbol                            | Parameter  | Test Conditions   | Min. | Typ.             | Max.      | Unit          |
|-----------------------------------|--|---|------|------------------|-----------|---------------|
| $I_{SD}$<br>$I_{SDM} (\bullet)$   | Source-drain Current<br>Source-drain Current (pulsed)                        |   |      |                  | 30<br>120 | A<br>A        |
| $V_{SD} (*)$                      | Forward On Voltage   | $I_{SD} = 30\text{ A}$ $V_{GS} = 0$   |      |                  | 1.5       | V             |
| $t_{rr}$<br>$Q_{rr}$<br>$I_{RRM}$ | Reverse Recovery Time<br>Reverse Recovery Charge<br>Reverse Recovery Current | $I_{SD} = 30\text{ A}$ $di/dt = 100\text{ A}/\mu\text{s}$<br>$V_{DD} = 30\text{ V}$ $T_j = 150^\circ\text{C}$<br>(see test circuit, Figure 5) |      | 65<br>155<br>4.8 |           | ns<br>nC<br>A |

(\*)Pulsed: Pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5 %.  
 (●)Pulse width limited by safe operating area.

Safe Operating Area for TO-220




Safe Operating Area for TO-220FP




**STP36NF06 STP36NF06FP**


Thermal Impedance




Thermal Impedance for TO-220FP




Output Characteristics




Transfer Characteristics




Transconductance




Static Drain-source On Resistance




Gate Charge vs Gate-source Voltage




Capacitance Variations




Normalized Gate Threshold Voltage vs Temperature




Normalized on Resistance vs Temperature




Source-drain Diode Forward Characteristics




Normalized Breakdown Voltage Temperature




**Fig. 1: Unclamped Inductive Load Test Circuit**




**Fig. 2: Unclamped Inductive Waveform**




**Fig. 3: Switching Times Test Circuits For Resistive Load**



**Fig. 4: Gate Charge test Circuit**




**Fig. 5: Test Circuit For Inductive Load Switching And Diode Recovery Times**




**TO-220FP MECHANICAL DATA**

| DIM. | mm   |      |      | inch  |       |       |
|------|------|------|------|-------|-------|-------|
|      | MIN. | TYP. | MAX. | MIN.  | TYP.  | MAX.  |
| A    | 4.4  |      | 4.6  | 0.173 |       | 0.181 |
| B    | 2.5  |      | 2.7  | 0.098 |       | 0.106 |
| D    | 2.5  |      | 2.75 | 0.098 |       | 0.108 |
| E    | 0.45 |      | 0.7  | 0.017 |       | 0.027 |
| F    | 0.75 |      | 1    | 0.030 |       | 0.039 |
| F1   | 1.15 |      | 1.7  | 0.045 |       | 0.067 |
| F2   | 1.15 |      | 1.7  | 0.045 |       | 0.067 |
| G    | 4.95 |      | 5.2  | 0.195 |       | 0.204 |
| G1   | 2.4  |      | 2.7  | 0.094 |       | 0.106 |
| H    | 10   |      | 10.4 | 0.393 |       | 0.409 |
| L2   |      | 16   |      |       | 0.630 |       |
| L3   | 28.6 |      | 30.6 | 1.126 |       | 1.204 |
| L4   | 9.8  |      | 10.6 | 0.385 |       | 0.417 |
| L6   | 15.9 |      | 16.4 | 0.626 |       | 0.645 |
| L7   | 9    |      | 9.3  | 0.354 |       | 0.366 |
| ∅    | 3    |      | 3.2  | 0.118 |       | 0.126 |



**TO-220 MECHANICAL DATA**

| DIM. | mm.   |       |       | inch. |       |       |
|------|-------|-------|-------|-------|-------|-------|
|      | MIN.  | TYP.  | MAX.  | MIN.  | TYP.  | TYP.  |
| A    | 4.4   |       | 4.6   | 0.173 |       | 0.181 |
| C    | 1.23  |       | 1.32  | 0.048 |       | 0.051 |
| D    | 2.40  |       | 2.72  | 0.094 |       | 0.107 |
| E    | 0.49  |       | 0.70  | 0.019 |       | 0.027 |
| F    | 0.61  |       | 0.88  | 0.024 |       | 0.034 |
| F1   | 1.14  |       | 1.70  | 0.044 |       | 0.067 |
| F2   | 1.14  |       | 1.70  | 0.044 |       | 0.067 |
| G    | 4.95  |       | 5.15  | 0.194 |       | 0.203 |
| G1   | 2.40  |       | 2.70  | 0.094 |       | 0.106 |
| H2   | 10    |       | 10.40 | 0.393 |       | 0.409 |
| L2   |       | 16.40 |       |       | 0.645 |       |
| L3   |       | 28.90 |       |       | 1.137 |       |
| L4   | 13    |       | 14    | 0.511 |       | 0.551 |
| L5   | 2.65  |       | 2.95  | 0.104 |       | 0.116 |
| L6   | 15.25 |       | 15.75 | 0.600 |       | 0.620 |
| L7   | 6.20  |       | 6.60  | 0.244 |       | 0.260 |
| L9   | 3.50  |       | 3.93  | 0.137 |       | 0.154 |
| DIA  | 3.75  |       | 3.85  | 0.147 |       | 0.151 |



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is registered trademark of STMicroelectronics  
All other names are the property of their respective owners.

© 2003 STMicroelectronics - All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -  
Malaysia - Malta - Morocco -Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.

[www.st.com](http://www.st.com)