

**7mm (0.3") SINGLE DIGIT  
NUMERIC DISPLAY**





**SUN LED**

Email : sales@us.sunled.com

Web Site : www.sunled.com

XDMR07A



**Notes:**


1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.25(0.01)$  unless otherwise noted.

Absolute maximum ratings ( $T_A=25^{\circ}\text{C}$ )		MR (GaAlAs)	Unit
Reverse voltage	$V_R$	5	V
Forward current	$I_F$	30	mA
Forward current (peak) 1/10Duty cycle 0.1ms pulse width	$i_{FS}$	155	mA
Power dissipation	$P_T$	100	mW
Operating temperature	$T_A$	-40 ~ +85	$^{\circ}\text{C}$
Storage temperature	$T_{stg}$		
Lead solder temperature [2mm below package base]	260 $^{\circ}\text{C}$ For 5 Seconds		

Operating Characteristics ( $T_A=25^{\circ}\text{C}$ )		MR (GaAlAs)	Unit
Forward voltage (typ.) ( $I_F=10\text{mA}$ )	$V_F$	1.8	V
Forward voltage (max.) ( $I_F=10\text{mA}$ )	$V_F$	2.5	V
Reverse current ( $V_R=5\text{V}$ )	$I_R$	10	$\mu\text{A}$
Wavelength at peak emission ( $I_F=10\text{mA}$ )	$\lambda_{\text{peak}}$	660	nm
Wavelength at Dominate emission ( $I_F=10\text{mA}$ )	$\lambda_D$	640	nm
Spectral Line half-width ( $I_F=10\text{mA}$ )	$\Delta\lambda$	20	nm
Capacitance ( $V_F=0\text{V}$ , $f=1\text{MHz}$ )	$C$	45	pF

Part Number	Emitting Color	Emitting Material	Luminous Intensity ( $I_F=10\text{mA}$ ) ucd		Wavelength nm $\lambda_P$	Description
			min.	typ.		
XDMR07A	Red	GaAlAs	12000	25990	660	Common Anode,Rt.Hand Decimal

**XDMR07A**



◆MR

