


Electrical test:
 1. 100% short, open, miswire test
 2. Conduct resistance: 2 Ohm(max)
 3. Insulation resistance: 10Mohm(min)
 4. dielectric test: DC 300V



Part Number
AK669M-X-R

Length
 1 1Meter
 2 2Meters

13	PACKING TAPE COLOR YELLOW L=2200mm			1/100	
12	TRANSPARENT ADHESIVE TAPE L=2600mm			1/100	
11	CARTON 5 LAYER 40*30*20CM K=K GLUE TYPE			1/100	
10	WATERPROOF BAG (14+15)*24" T=0.04mm			1/100	
9	PE BAG 230*300*0.04mm PRINT BLACK"MADE IN CHINA"+10PCS			1/10	
8	PE BAG 100*200*0.04mm PRINT BLACK"MADE IN CHINA"	1	PCS		
7	ROHS LABEL 35*22mm WHITE/BOTTOM TEXT/BLACK			112/100	
6	INNER MODEL LDPE	4	g		
5	OUTER MODEL PVC 45P COLOR BLACK(CS-001)	9	g		
4	ROUND TIN OD.8mm	0.4	g		
3	USB MINI USB5P/M SOLDER TYPE PLASTIC BLACK	1	P2		
2	USB MINI USB5P/F SOLDER TYPE PLASTIC BLACK	1	P1		
1	USB UL2725 28AW*1P+28AW*2C+AL/MY+D+B0D3.8mm BLACK(CS-001)	01	1	2000mm	
NO.	PART NO.	DESCRIPTION	VENDER	QTY	UNIT/REF

REV	REV./NO.	DESCRIPTION	DATE
		ASSMANN Electronics, Inc.	TITLE: MIN USB5P/F TO MIN USB5P/M CABLE 1000mm Version 1.1
DRAW			DWN NO.
JE			REV A
CONFIRM			REV
DIRECTOR			CUS. P/N:
CONFIRM			CUS. X013
MANAGER			APPROVAL
APPROVAL			SHEET 1 to 1
SL			

QMP010-08-A