

ISO 9001 Certified Manufacturer




## Surface Mount Battery Clip

For "A", "AA", "AAA", "AAAA" and "N" Cells  
Available in Low Profile Design




[View  
Catalog Pg\(s\)](#)



This series of Low Profile SMT Battery Clips for "A", "AA", "AAA", "AAAA" and "N" cells are especially useful in high density package applications.

Manufactured using .010 (0.25mm) or .012 (0.30mm) thick Nickel Plated Spring Steel, these clips are designed to securely retain cells and withstand shock and vibration, they also feature a "Flow Hole" SMT solder tail designed to increase joint strength.

These clips are available in loose piece (Catalog Numbers 50, 53 and 55), or on Tape and Reel (Catalog Numbers 50TR, 53TR and 55TR), on 13 inch or 15 inch reels. The carrier tape is polystyrene, with parts mounted on a 16mm or 24mm pitch, that meets ANSI/EIA-481 standards.



### "AAA" or "N" Cell Clip Specifications

[Clip and Contact Mounting Bulletin](#) - For detailed mounting options and alternate board layout configurations.

### "AAAA" Cell Clip Specifications

Availability is from stock through Keystone's [Global Distributor Network](#). Application engineering services are available to meet special customer requirements.

Refer to Keystone's Catalog M55 for our complete product offering and specifications.

### "A" or "AA" Cell Clip Specifications

For detailed drawings, specifications and applications data, [Contact Us](#) by e-mail or please contact our Customer Service Department at (800) 221-5510 or (718) 956-8900 or by Fax (718) 956-9040.