

MINI-PS-120-230AC/24DC/0.65

This product has been replaced by a newer version.

Order No.: 2938497



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2938497>

Power supply unit, primary switched-mode

Commercial data

EAN	4017918607555
Pack	1 Pcs.
Customs tariff	85044081
Weight/Piece	0.2046 KG
Catalog page information	Page 413 (IF-2002)

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Input data

Nominal input voltage	100 V AC ... 240 V AC
AC input voltage range	85 V AC ... 264 V AC
DC input voltage range	90 V DC ... 350 V DC
AC frequency range	47 Hz ... 63 Hz
DC frequency range	0 Hz
Current consumption	Approx. 0.2 A (at 230 V AC, nominal load) Approx. 0.4 A (at 120 V AC, nominal load)
Inrush surge current	< 10 A (at 25°C, < 1 ms)

Power failure bypass	> 30 ms (for 120 V AC)
	> 100 ms (for 230 V AC)
Input fuse	Internal
Output data	
Nominal output voltage	24 V DC \pm 3%
Output current	0.65 A (up to 60°C)
	Up to 1.2 A (with POWER BOOST)
Connection in parallel	Yes, for assembling redundant systems
Residual ripple	< 100 mVPP
Peak switching voltages nominal load	< 20 mVPP (20 MHz)
Maximum power dissipation idling	2.2 W
Power loss nominal load max.	3.2 W
General data	
Width	22.5 mm
Height	99 mm
Depth	114.5 mm
Weight	0.14 kg
Efficiency	> 80 % (for 230 V AC and nominal values)
Insulation voltage input/output	3 kV (routine test)
	4 kV (type test)
Degree of protection	IP20
Class of protection	II (in an enclosed control cabinet)
MTBF	> 500 000 h in acc. with IEC 61709 (SN 29500)
Ambient temperature (operation)	-25 °C ... 60 °C (UL up to 50°C)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	95 % (at 25°C, no condensation)
Mounting position	On horizontal DIN rail NS 35 in acc. with EN 60715
Assembly instructions	Can be aligned: Vertical with spacing > 10 cm, horizontal with zero spacing
Electromagnetic compatibility	Conformance with EMC directive 89/336/EEC
Standard - Electrical safety	EN 60950/VDE 0805 (SELV)
Standard - Safe isolation	DIN VDE 0100-410
	DIN VDE 0106-1010

Connection data, input

Type of connection	COMBICON screw/plug connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	14
Stripping length	7 mm
Screw thread	M 3

Connection data, output


Type of connection	COMBICON screw/plug connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	14
Stripping length	7 mm

Signaling


Status display	LED green (DC OK = LED permanently lit)
----------------	---

Drawings

Diagram



Circuit diagram



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2008 Phoenix Contact
Technical modifications reserved;