# Waber-by-TrippLite SurgeSuppressor

Heavy-dutymetalhousing



### DESCRIPTION

Model#:PM6NS

- 6outlets/6ft.cord
- 🕨 450joules

The Waber -by-Tripp Lite PM6NS Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Includes 6 NEMA 5 -15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installationinawidevarietyofapplications. Protectsconnected equipment from transient surges and line noise with built insurge suppression rated at 450 joules. Corded, multi -outlets trip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wallsocket. Features metal housing, lighted powers witch with integrated 15 ampresettable circuit breaker and attractive beigehousing with blackout put receptacles and power cord. Lifetime warranty.

PLUG/OUTLETS -Input:NEMA5 -15P/Output:6NEMA5 -15R

ELECTRICAL -120VAC, 50/60Hz, 15A(RequiresstandardNEMA5 -15Rwallreceptacle)

FORMAT -Cordedpowerdistributionstripwithsurgesuppression

SUPPRESSION -450joulesACsuppression

#### **KEYBUYINGPOINTS**

- Multi-outletpowerstripoffersconvenientpowerdistributioninworkbench,wallmountorfloormountapplications
- Includes6NEMA5 -15Routputreceptacles
- Lightedcombinationpowerswitchwithintegratedcircuitbreaker
- Keyholemountingtabssupportpermanentinstallationonawidevarietyofsurfaces
- UL1449(USA/400Vrating),UL1363(USA),cUL(Canada)
- 15amppowerhandlingcapacity
- 6footAClinecord
- Lifetimewarranty

#### **TYPICALAPPLICATIONS**

• Offers multiple outlet power distribution and surge suppression in workbench, wallmount or floor mount applications. Ideal protection for home appliances, entertainment centers, industrial equipment and other electronic loads.

#### PACKAGEINCLUDES

- PM6NSPowerStrip
- Warrantyinformation
- Instructionmanual

## COMPLETESPECIFICATIONS

SYSTEMOVERVIEW	
Voltagecompatibility:	120VAC
Frequencycompatibility:	50/60Hz
Ουτρυτ	
Outputvoltampcapacity(amps):	15
Outputwattcapacity(watts):	1800
Outletquantity/type:	6NEMA5 -15Routputreceptacles
INPUT	
Inputconnectiontype:	NEMA5 -15Pinputplug
Inputcordlength(ft.):	6
Inputcordlength(m):	1.8
Inputcordgauge,type:	14gauge,SJT
Recommendedelectricalservice:	120V15A
LEDSALARMS&SWITCHES	
DiagnosticLEDs:	Protectionpresent(green)
Switches:	Lightedtwopositionpowerswitchcontrolspowertoalloutlets
ACSURGE/NOISESUPPRESSION	
Protectionmodes:	Includesfullnormalmode(H -N)andcommonmode(N -G/H -G)linesurgesuppression
ACsuppressionjoulerating:	450joules
UL1499letthroughrating:	400V -ULVerified
EMI/RFIfiltering:	Upto20dB
Immunity:	ConformstoIEE587/ANSIC62.41
PHYSICAL	
UnitDimensions(HWD/in):	12.5x2.5x1.5
UnitDimensions(HWD/cm):	31.75x6.35x3.8
Materialofconstruction:	Metal
Integratedkeyholemountingtabs:	Keyholemountingtabsenablewallmounting
Housingcolor:	Beige
Receptaclecolor:	Black
AClinecordcolor:	Black
CERTIFICATIONS	
UL14491998Rev.(ACSuppression):	UL1449
UL1363(PowerTap):	UL1363
cUL/CSA(Canada):	cUL
WARRANTY	
Productwarranty:	Lifetime

ThepolicyofTrippLiteisoneofcontinuousimprovement. Specificationsaresubjecttochangewithoutnotice. Therefore,yourproductmayvaryslightlyfromwhatiscurrentlylisted. Pleasemakenotethatthisinformationwaspostedon08/04/2003.



TrippLiteWorldHeadquarters 1111W.35thStreet Chicago,IL60609USA

> CustomerSupport (773)869 -1234

© 2003TrippLite.AllRightsReserved.