Waber-by-TrippLite SurgeSuppressor

Heavy-dutymetalhousing



Model#:PM6SN1

- 6outlets/6ft.cord
- 450joulerating

DESCRIPTION

The Waber -by-Tripp Lite PM6SN1 Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Includes 6 NEMA 5 -15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installationinawidevarietyofapplications. Protects connected equipment from transient surges and line noise with built insurge suppression rated at 450 joules. Corded, multi -outlets trip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted powers witch with integrated 15 ampresettable circuit breaker and attractive beigehousing with blackout put receptacles and power cord. Life time warranty.

PLUG/OUTLETS -Input:NEMA5 -15P/Output:6NEMA5 -15R

ELECTRICAL -120VAC,50/60Hz,15A(RequiresstandardNEMA5 -15Rwallreceptacle)

FORMAT -Cordedpowerdistributionstripwithsurgesuppression

SUPPRESSION -450joulesACsuppression

KEYBUYINGPOINTS

- Multi-outletpowerstripoffersconvenientpowerdistributioninworkbench, wallmountorfloormountapplications
- Includes6NEMA5 -15Routputreceptacles
- Lightedcombinationpowerswitchwithintegratedcircuitbreaker
- Keyholemountingtabssupportpermanentinstallationonawidevarietyofsurfaces
- UL1449(USA/400Vrating),UL1363(USA),cUL(Canada)
- 15amppowerhandlingcapacity
- 6footAClinecord
- Lifetimewarranty

TYPICALAPPLICATIONS

• Offers multiple outlet power distribution and surge suppression in workbench, wall mount or floor mount applications. Ideal protection for home appliances, entertainment centers, industrial equipment and other electronic loads.

PACKAGEINCLUDES

- PM6SN1PowerStrip
- Warrantyinformation
- Instructionmanual

COMPLETESPECIFICATIONS

YSTEMOVERVIEW	
oltagecompatibility:	120VAC
equencycompatibility:	50/60Hz
UTPUT	
utputvoltampcapacity(amps):	15
utputwattcapacity(watts):	1800
utletquantity/type:	6NEMA5 -15Routputreceptacles
IPUT	
putconnectiontype:	NEMA5 -15Pinputplug
putcordlength(ft.):	6
putcordlength(m):	1.8
putcordgauge,type:	14gauge,SJT
ecommendedelectricalservice:	120V15A
LEDSALARMS&SWITCHES	
agnosticLEDs:	Protectionpresent(green)
witches:	Lightedtwopositionpowerswitchcontrolspowertoalloutlets
ACSURGE/NOISESUPPRESSION	
rotectionmodes:	Includesfullnormalmode(H -N)andcommonmode(N -G/H -G)linesurgesuppression
Csuppressionjoulerating:	450joules
L1499letthroughrating:	400V -ULVerified
MI/RFIfiltering:	Upto20dB
nmunity:	ConformstoIEE587/ANSIC62.41
HYSICAL	
nippingweight(lbs):	1.5
hippingweight(kg):	0.7
nitweight(lbs):	1.25
nitweight(kg):	0.6
nitDimensions(HWD/in):	12.5x2.5x1.5
nitDimensions(HWD/cm):	31.75x6.35x3.8
aterialofconstruction:	Metal
tegratedkeyholemountingtabs:	Keyholemountingtabsenablewallmounting
ousingcolor:	Beige
•	Black
Clinecordcolor:	Black
ERTIFICATIONS	
(11 /	UL1449
` ''	UL1363
,	cUL
ARRANTY	
roductwarranty:	Lifetime

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.

Please make note that this information was posted on 08/04/2003.



TrippLiteWorldHeadquarters 1111W.35thStreet Chicago,IL60609USA

> CustomerSupport (773)869 -1234

© 2003TrippLite.AllRightsReserved.